




**Ash Gray**  
 SR 0.46 | SRI 52



**Colony Green**  
 SR 0.28 | SRI 27 | Only 26ga.




**Burnished Slate**  
 SR 0.34 | SRI 35



**Charcoal Gray**  
 SR 0.37 | SRI 39



**Hawaiian Blue**  
 SR 0.31 | SRI 31 | Only 26ga.



**Polar White**  
 SR 0.64 | SRI 77

The Weather XL™ Silicone Polyester coil coatings from Sherwin Williams are ideal for agricultural, industrial, and pre-engineered metal building components and systems.

- Recognized for its remarkable color and gloss retention as well as its superior chalk resistance.
- A two-coat system that is highly resistant to stains, abrasion, and metal marking.

PROUDLY FINISHED WITH  
**SHERWIN-WILLIAMS**  
 Coil Coatings



valspar



**Evergreen**  
 SR 0.35 | SRI 37



**Light Stone**  
 SR 0.56 | SRI 65



**Saddle Tan**  
 SR 0.47 | SRI 53



**Desert Sand**  
 SR 0.42 | SRI 47 | Only 29ga.



**Koko Brown**  
 SR 0.35 | SRI 37



**Rustic Red**  
 SR 0.36 | SRI 38

### Solar Reflectivity (SR) and Solar Reflectance Index (SRI) by Color

**Solar reflectivity** or reflectance is the ability of a material to reflect solar energy from its surface back into the atmosphere. The SR value is a number from 0 to 1.0. A value of 0 indicates that the material absorbs all solar energy and a value of 1.0 indicates total reflectance.

**Energy Star** requires an initial SR value of 0.25 or higher for steep slope (>2:12) roofs and 0.15 or greater after three years. Low slope roofs require an initial SR value of 0.65 or higher and 0.50 or greater after three years.

The **Solar Reflectance Index** is used for compliance with **LEED** requirements and is calculated according to ASTM E 1980 using values for reflectance and emissivity.

Emissivity is a material's ability to release absorbed energy. To meet **Energy Star** requirements a roofing material must have a SRI of 29 or higher to meet steep slope (>2:12) roofing and a SRI value of 78 or higher for low slope roofing.



Colors listed above are intended to be close representations. Actual color chips are available upon request. Please verify color, gauge, and profile availability.